

## PRODUCT OVERVIEW

Clado Fix Superemo is a new age polymer modified adhesive for fixing natural stones, tiles etc. on floor and walls with supreme strength and adhesion.

PRODUCT BENEFITS	PACKING
<ul style="list-style-type: none"> <li>» Polymer Modified Adhesive</li> <li>» User Friendly</li> <li>» For Both Exterior &amp; Interior</li> <li>» For Fresh Concrete/plaster Surface</li> <li>» Suitable For All Type Of Stone And Tiles</li> <li>» Including Flyash Bricks</li> </ul>	<p>■ 25 Kg.</p>
PRODUCT FEATURES	
<ul style="list-style-type: none"> <li>■ Water and Heat Proof</li> <li>■ Easy Flow &amp; Workability</li> <li>■ Excellent Adhesion to all Conventional Materials Used in Building</li> <li>■ Highly Thixotropic To Avoid Slip</li> </ul>	

TECHNICAL SPECIFICATION			
<b>Dry Set To Touch</b>	<b>Bulk Density</b>	<b>Appearance</b>	<b>Water Mixing Ratio</b>
60 Min	1.15 Kg/Ltr.	White Powder	400-450 ml/per Kg.
<b>Water Permiability</b>	<b>Complete Curing</b>		<b>Surface Drying Time</b>
Negligible	24 Hours @ 30° C		30 - 40Min @ 30° C
<b>Storage &amp; Pot Life</b>	<b>Adhesion Strength</b>		<b>Approx Coverage Per 25 Kg. Bag</b>
24 Months @ 25°C Keep in cool and Dry place	.94 Mpa - 7 days 1.49 Mpa - 28 days		If 6mm - 2 - 2.25 Sq.Mtr (20-24 Sq.Ft.) If 3mm - 4.5 - 5.5 Sq.Mtr (48-60 Sq. Ft.) If 2mm - 8.5 - 9.5 Sq.Mtr (90-100 Sq. Ft.)

## PROTECTION

- All Substrates Should Be Structurally Sound, Stable , Dry, Clean And Free Of Any Substance Or Condition That May Reduce Or Prevent Proper Adhesion.
- Protect from traffic for 24 to 48 hours. Protect from heavy traffic for 7 Days.
- Protect from humidity and rain for 7 days.
- Glass mosaic tile required at least 21 days of curing time after grouting before filling water in the pool.

## SURFACE PREPARATION

- Clean the surface thoroughly as it should be free fro dust, dirt, oil grease etc.
- For good coverage ensure that the new plaster should be flat enough for levelling finish.
- All tiles and other porous or non- porous surface should be cleaned & washed with clean water.

## Thinner / Cleaning Solvent

Water

## Caution

The applicators and operators must be trained, experienced and have the understanding and equipment to mix/stir and apply the coatings correctly and according to Nushar technical protocol. Applicators and operators shall use appropriate personal protection areas when using these products.

## Health and safety

Please study the safety precautions mentioned on the container. Apply the products under well ventilated conditions. Ensure that spray mist is not inhaled and skin contact with the product should be avoided. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. If the eyes feel any burning sensation then they should be flushed with ample water and the Doctor should be immediately consulted

Note: We do not undertake any legal obligation for the product as its proper application is equally important. We accept no legal responsibility for the work done ever by trained applicators as we have no control over what they are actually doing on the site. The consumer has to first satisfy himself/herself by observing work done by us & by visiting our display gallery. All subject to the jurisdiction of courts in Jodhpur, Rajasthan.

**Note : The Product material can be renewed by the company for the betterment at anytime without any notice/information.**