

PRODUCT OVERVIEW

White Fix Ease is a Fine White Powder Composed Of Cement, Graded Aggregates, Synthetic n Special Nano Additives & Polymers New Age Polymerised Adhesive For Fixing Natural Stones Tiles on Floor & Walls with Supreme Strength, Adhesion & Weather Proofing

PRODUCT BENEFITS	PACKING
<ul style="list-style-type: none"> ➤ Polymer Modified Adhesive ➤ User Friendly ➤ For Both Exterior & Interior ➤ For Fresh Concrete/plaster Surface ➤ Suitable For All Type Of Stone And Tiles ➤ Including Flyash Bricks 	<p>■ 25 Kg.</p> 
PRODUCT FEATURES	
<ul style="list-style-type: none"> ■ Water & Heat Proof ■ Easy Flow & Workability ■ Excellent Adhesion To All Conventional Materials Used In Building ■ Highly Thixotropic/Viscous To Avoid Slip 	

TECHNICAL SPECIFICATION			
Dry Set To Touch	Bulk Density	Appearance	Water Mixing Ratio
60 Min	1.15 Kg/Ltr.	White Powder	400-450 ml/per Kg.
Water Permiability	Complete Curing		Surface Drying Time
Negligible	24 Hours @ 30° C		30 - 40Min @ 30° C
Storage & Pot Life	Adhesion Strength		Approx Coverage Per 25 Kg. Bag
24 Months @ 25°C Keep in cool and Dry place	.94 Mpa - 7 days 1.49 Mpa - 28 days		If 6mm - 2 -2.25 Sq.Mtr (20-24 Sq.Ft.) If 3mm - 4.5 - 5.5 Sq.Mtr (48-60 Sq. Ft.) If 2mm - 8.5 - 9.5 Sq.Mtr (90-100 Sq. Ft.)

PROTECTION

- Protect from traffic for 24 to 48 hours. Protect from heavy traffic for 7 days.
- All glass installations benefit from extended cure times before grouting or permitting foot traffic.
- Protect from humidity and rain for 7 days.
- Glass mosaic tile requires at least 21 days of curing time after grouting before filling water in the pool.

HOW TO USE

- All Substrates Should Be Structurally Sound, Stable, Dry, Clean And Free Of Any
- Substance Or Conditon That May Reduce Or Prevent Proper Adhesion.
- Approx 400-500ml Water To Be Mixed in 1Kg. White Fix ease
- Apply The Mortar On Both Surface With The Help Of Teethed Trowel For Better Adhesion.

Thinner / Cleaning Solvent

Water

Caution

The applicators and operators must be trained, experienced and have the understanding and equipment to mix/stir and apply the coatings correctly and according to Nushar technical protocol. Applicators and operators shall use appropriate personal protection areas when using these products.

Health and safety

Please study the safety precautions mentioned on the container. Apply the products under well ventilated conditions. Ensure that spray mist is not inhaled and skin contact with the product should be avoided. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. If the eyes feel any burning sensation then they should be flushed with ample water and the Doctor should be immediately consulted

Note: We do not undertake any legal obligation for the product as its proper application is equally important. We accept no legal responsibility for the work done ever by trained applicators as we have no control over what they are actually doing on the site. The consumer has to first satisfy himself/herself by observing work done by us & by visiting our display gallery.

All subject to the jurisdiction of courts in Jodhpur, Rajasthan.

Note : The Product material can be renewed by the company for the betterment at anytime without any notice/information.